

WQR 系列耐高温排污泵



郑州市神龙泵业有限公司

ZHENGZHOSHENLONGSUBMERSIBLE PUMP CO.,LTD

WQR耐高温排污泵

用途：

- 1、锅炉水输送。
- 2、酒店洗衣房排水。
- 3、电厂、钢铁厂抽送热水。

使用条件：

1. 介质温度不超过100℃，密度为1.0-1.3kg/m³。
2. 电机部分露出液面不超过1/2。
3. 泵必须在使用扬程范围内使用，保证电机不过载。

型号意义：



特点：

- 1、耐高温电机。
- 2、耐高温进口轴承、耐高温机械密封。
- 3、耐高温O型圈和耐高温电缆线。
- 4、此款泵壳是铁铸材质，如果需要不锈钢的也可以定制。



性能参数表

编号	型号	额定流量 (m ³ /h)	额定扬程 (m)	功率 (kW)	口径 (mm)	电压 (V)	转速 (r/min)
1	25WQR5-18-0.75	5	18	0.75	25	220	2900
2	32WQR6-16-0.75	6	16	0.75	32	220	2900
3	40WQR7-15-0.75	7	15	0.75	40	220	2900
4	50WQR10-10-0.75	10	10	0.75	50	220	2900
5	40WQR7-18-1.1	7	18	1.1	40	220	2900
6	50WQR9-15-1.1	9	15	1.1	50	220	2900
7	65WQR15-9-1.1	15	9	1.1	65	220	2900
8	50WQR15-15-1.5	15	15	1.5	50	220	2900
9	65WQR25-7-1.5	25	7	1.5	65	220	2900
10	80WQR40-8-1.5	40	8	1.5	80	220	2900
11	50WQR15-20-2.2	15	20	2.2	50	220	2900
12	65WQR20-15-2.2	20	15	2.2	65	220	2900
13	80WQR40-10-2.2	40	10	2.2	80	220	2900
14	100WQR50-7-2.2	50	7	2.2	100	220	2900
15	50WQR15-30-3	15	30	3	50	220	2900
16	65WQR37-13-3	37	13	3	65	220	2900
17	80WQR45-12-3	45	12	3	80	220	2900
18	100WQR60-9-3	60	9	3	100	220	2900
19	50WQR15-35-4	15	35	4	50	220	2900
20	65WQR20-25-4	20	25	4	65	220	2900

WQR耐高温排污泵

性能参数表

编号	型号	额定流量 (m³/h)	额定扬程 (m)	功率 (kW)	口径 (mm)	转速 (r/min)
21	80WQR40-15-4	40	15	4	80	2900
22	100WQR60-12-4	60	12	4	100	2900
23	50WQR20-40-5.5	20	40	5.5	50	2900
24	65WQR25-35-5.5	25	35	5.5	65	2900
25	80WQR30-30-5.5	30	30	5.5	80	2900
26	100WQR65-18-5.5	65	18	5.5	100	2900
27	150WQR100-10-5.5	100	10	5.5	150	2900
28	50WQR20-50-7.5	20	50	7.5	50	2900
29	65WQR30-40-7.5	30	40	7.5	65	2900
30	65WQR40-30-7.5	40	30	7.5	65	2900
31	80WQR65-25-7.5	65	25	7.5	80	2900
32	100WQR80-15-7.5	80	15	7.5	100	100
33	150WQR100-15-7.5	100	15	7.5	150	2900
34	200WQR250-6-7.5	250	6	7.5	200	1450
35	50WQR20-60-11	20	60	11	50	2900
36	65WQR30-50-11	30	50	11	65	2900
37	80WQR40-40-11	40	40	11	80	2900
38	100WQR80-25-11	80	25	11	100	2900
39	100WQR100-25-11	1000	25	11	100	1450
40	150WQR150-12-11	150	12	11	150	2900
41	150WQR130-15-11	130	15	11	150	1450
42	200WQR200-9-11	200	9	11	200	2900
43	200WQR300-7-11	300	7	11	200	1450
44	50WQR30-60-15	30	60	15	50	2900
45	65WQR35-55-15	35	55	15	65	2900
46	80WQR45-52-15	45	52	15	80	2900
47	100WQR60-45-15	60	45	15	100	2900
48	100WQR100-30-15	100	30	15	100	1450
49	150WQR150-20-15	150	20	15	150	2900
50	150WQR180-15-15	180	15	15	150	1450

编号	型号	额定流量 (m³/h)	额定扬程 (m)	功率 (kW)	口径 (mm)	转速 (r/min)
51	200WQR250-11-15	250	11	15	200	2900
52	200WQR200-12-15	200	12	15	200	1450
53	100WQR100-35-18.5	100	35	18.5	100	1450
54	150WQR180-20-18.5	180	20	18.5	150	1450
55	200WQR250-15-18.5	250	15	18.5	200	1450
56	250WQR400-7-18.5	400	7	18.5	250	1450
57	100WQR100-40-22	100	40	22	100	1450
58	150WQR200-22-22	200	22	22	150	1450
59	150WQR180-25-22	180	25	22	150	1450
60	200WQR300-15-22	300	15	22	200	1450
61	200WQR400-10-22	400	10	22	200	1450
62	250WQR500-7-22	500	7	22	250	1450
63	100WQR120-45-30	120	45	30	100	1450
64	150WQR180-30-30	180	30	30	150	1450
65	150WQR250-22-30	250	22	30	150	1450
66	200WQR400-13-30	400	13	30	200	1450
67	250WQR600-9-30	600	9	30	250	1450
68	300WQR800-7-30	800	7	30	300	1450
69	100WQR120-50-37	120	50	37	100	1450
70	150WQR200-30-37	200	30	37	150	1450
71	200WQR350-25-37	350	25	37	200	1450
72	250WQR600-12-37	600	12	37	250	1450
73	300WQR800-10-37	800	10	37	300	1450
74	350WQR1000-6-37	1000	6	37	350	1450
75	100WQR100-57-45	100	57	45	100	1450
76	150WQR200-35-45	200	35	45	150	1450
77	200WQR400-25-45	400	25	45	200	1450
78	250WQR600-15-45	600	15	45	250	1450
79	300WQR800-12-45	800	12	45	300	1450
80	350WQR1200-8-45	1200	8	45	350	1450



神武[®]
SHEN WU

郑州市神龙泵业有限公司

ZHENGZHOU SHENLONG SUBMERSIBLE PUMP CO.,LTD

地址：中国·河南·郑州市高新技术开发区冬青街 26 号河南电子商务产业园 6 号楼

邮编：450052

电话：0371-55356761、55356762

传真：0371-55356763

网址：<http://www.hnshenwu.com>

生产基地：荥阳广高公路西段